ALLinONE Solution

It's never been so easy to get the most from solar cells

Just connect the output cable to your battery.

Solar panel and charge controller. To make solar energy simpler, suitable for the enthusiast as well as the professional user.


All the electronics you need are already packed into the rugged waterproof box: a sophisticated **MPPT controller** capable of boosting the voltage to match with your battery pack.

With the ALLinONE solution, panels can be combined simply by connecting them directly to your battery, each one being **completely independent** from the others, thanks to the integrated charge controller.













The panels












	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Peak Power (W)	Battery Voltage (V)	Maximum Current (A)	N. of Cells
SP 19 AiO	728	546	15	1,1	65	12/24	5/2,5	19
SP 15 L Ai0	1109	292	15	0,9	51	12/24	4/2	15
SP 15 Q AiO	601	546	15	0,9	51	12/24	4/2	15
SP 7 AiO	600	292	15	0,6	24	12/24	2/1	7







	Length (mm)	Width (mm)	Thickness (mm)	Weight (kg)	Peak Power (W)	Battery Voltage (V)	Maximum Current (A)	N. of Cells
SR 19 AiO	881	694	15	1,7	95	12/24	8/4	19
SR 15 L AiO	1366	371	15	1,3	75	12/24	6/3	15
SR 15 Q AiO	719	694	15	1,3	75	12/24	6/3	15

